



Cut- and bendmachine MSBC40-46E, 3x 400V-50Hz

510.10530

Features:

- Electrically driven cut- and bend machine for rebar.
- Simple and robust design with two adjustable guides.
- The bending plate can rotate both left and right.
- The cutting head is equipped with 2 hardened steel blades that are changeable.
- Angle adjustment by means of stop pins (1 bending angle per direction of rotation).

Bending tools included:

- 7 bending rollers (Ø50-60-70-80-95-120-150mm)
- 3 bending pins
- 1 stirrup bending tool
- 1 small diameter bending pin
- 1 foot pedal

Technical information:

- RPM: 6

- Motor capacity: 4 KW at 3 ϕ 400V/50Hz
- Max. bending capacity at R=650 N/mm²: 1 $\times$ Ø34, 2 $\times$ Ø24, 3 $\times$ Ø20mm
- Max. bending capacity at R=850 N/mm²: 1 $\times$ Ø32, 2 $\times$ Ø22, 3 $\times$ Ø18mm
- Max. cutting capacity at R=650 N/mm²: 1 $\times$ Ø28, 2 $\times$ Ø20, 3 $\times$ Ø16mm
- Max. cutting capacity at R=850 N/mm²: 1 $\times$ Ø25, 2 $\times$ Ø16, 3 $\times$ Ø14mm
- L $\times$ W $\times$ H: 105 $\times$ 120 $\times$ 90cm
- Weight: 620 kg