



Cut- and bendmachine MSBC32-36E, 3x 400V-50Hz

510.10520

Features:

- Electrically driven bending machine for rebar.
- Simple and robust design with two adjustable guides.
- The bending plate can rotate both left and right.
- The cutting head is equipped with 2 hardened steel blades that are changeable.
- Angle adjustment by means of stop pins (1 bending angle per direction of rotation).

Bending tools included:

- 6 bending rollers (Ø50-60-70-80-95-120mm)
- 3 bending pins
- 1 stirrup bending tool
- 1 small diameter bending pin
- 1 foot pedal

Technical information:

- RPM: 8
- Motor capacity: 3 KW at 3 ϕ 400V/50Hz
- Max. bending capacity at R=650 N/mm²: 1 \times Ø34, 2 \times Ø24, 3 \times Ø20mm
- Max. bending capacity at R=850 N/mm²: 1 \times Ø32, 2 \times Ø22, 3 \times Ø18mm
- Max. cutting capacity at R=650 N/mm²: 1 \times Ø28, 2 \times Ø20, 3 \times Ø16mm
- Max. cutting capacity at R=850 N/mm²: 1 \times Ø25, 2 \times Ø16, 3 \times Ø14mm
- L \times W \times H: 90 \times 107 \times 85cm
- Weight: 400 kg