

## Bending machine MSB74-E, 3x400V-50Hz, 2-speed, with controller

510.10373

Features:

- · Electrically driven bending machine for rebar.
- $\cdot$  Simple and robust design with two adjustable guides.
- $\cdot$  The bending plate can rotate both left and right.
- $\cdot$  Two bending speeds allow for higher speed when bending thinner diameters.
- $\cdot$  Angle adjustment by means of programmable display. Bending shapes consisting of several different bending angles, both positive and negative (up to 20 pieces) in one cycle.
- $\cdot$  In addition, a counter is provided to count the number of bends.

Bending tools included:

- · 7 bending rollers (Ø80-95-110-150-200-240-300mm)
- $\cdot$  3 bending pins
- $\cdot$  1 stirrup bending tool
- $\cdot$  1 small diameter bending pin
- · 1 foot pedal

Technical information:

· RPM: 5

- $\cdot$  Motor capacity: 7.5 KW at 3 $\phi$  400V/50Hz
- · Max. bending capacity at R=650 N/mm<sup>2</sup>:  $1 \times \emptyset$ 60,  $2 \times \emptyset$ 42,  $3 \times \emptyset$ 34mm
- · Max. bending capacity at R=850 N/mm<sup>2</sup>:  $1 \times 050$ ,  $2 \times 036$ ,  $3 \times 030$ mm
- · L×W×H: 160×116×96cm
- · Weight: 1600 kg

Control panel: